Brodit
DEVICE MOUNTING SOLUTIONS



Active holder for fixed installation

With tilt swivel. 2.5A charging. 12/24V. With Easy-switching system. Charging via pogo pins.Fits device with Datalogic original RUBBER BOOT.

Item no: 713430
EAN Number: 7320287134308

An active holder which is to be connected inside the dashboard, this gives a discreet, neat installation without cables hanging over the interior! You can choose to use the holder as an active holder for charging of your device only, or to connect an adapter to the Molex connector for additional features. Then you can use the holder also for power supply of a GPS receiver or other own solutions (can not be used for data communication or audio connection). 12/24 Volt. The product is E-approved. Connect the power cable with a 2.5 A fuse. 2 A charger. Professional installation recommended.

Easy-switching system:
The easy-switching system enables you to upgrade the holder only, and keep the installed cables. It saves you a lot of time! When upgrading to a new device, you do not longer need to make a full installation. Same goes for maintenance in case of warranty or damage. You simply disconnect the holder from the charging cable via the Molex 6-pin quick connector, and then connect the new holder. The switch is done in a few seconds.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Connect the power cable with a 3A fuse. Professional installation recommended. Attach onto a ProClip Mounting Platform or a Pedestal Mount.

Fits the following models:
Datalogic Memor 12-17

For a complete list, see
www.brodit.com/en/product/713430

Measurements:
Height 108 mm
Width 90 mm
Depth 64 mm
Volume 622 cm³
Weight 304 g

Charging specifications:
- Input voltage: DC/10-30V
- Charging voltage: DC/4.75-5.3V
- Output current (Typ): 2.5A
- Input & output protection: Input polarity reversal/Output over voltage/Output over current/Output shortprotection
- LED charging indicator: Power input indicator(Green), Ovp/Ocp/Output short (Red)
- Operating temperature: 0°C ~ +40°C
- Storage temperature: -20°C ~ +60°C
- RoHS compliant: CE, E-mark, FCC, RoHS