Brodit
DEVICE MOUNTING SOLUTIONS



Active holder for fixed installation

With USB-C cable. 2 USB-A ports: QC 3.0A + 2.4A. With tilt swivel. 12/24 Volt.

Item no: 727422
EAN Number: 7320287274226

Keep your phone's battery fully charged in an active holder, always within easy sight and reach! Neat, discreet and convenient. Custom made with a perfect, firm fit. For fixed installation. The holder is to be connected inside the dashboard, providing an elegant installation without any cables hanging over the interior. The charging box has two USB ports Type A, Type C. You have full access to the camera and all buttons when the device is in the holder. It is easy to slide the phone in place in the holder so it connects to the charging, and to take it out of the holder when leaving the vehicle.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Connect the power cable with a 2A fuse. Professional installation recommended. Attach onto a ProClip mounting platform.

Fits the following models:
Datalogic Memor 30
Datalogic Memor 35

For a complete list, see
www.brodit.com/en/product/727422

Measurements:
Height 110 mm
Width 85 mm
Depth 57 mm
Volume 533 cm³
Weight 267 g

Charging specifications:
- Output Connector Type: USB-A + TYPE-C PD
- Output Voltage: 5V,9 V,12 V (Nominal)
- Output Current:
- USB Port 1: TYPE-C PD:3.6V ~ 6V/3A 6.2-9V/2A 9.2-12V/1.5A(Under full Load)
- USB Port 2: USB-A Port 2:5V/3A 9V/2A 12V/1.5A(No Device attached)
- Output Voltage Ripple: 300mV pk-pk at Max Load
- Input Voltage Range: DC 12--24V DC,Input can handle 40V Load dump translent events
- Input Current: 3.0 A DC Max
- Input Current with No device attached: 0.005A
- DC-DC Conversion Efficiency: Over 86% Typical
- Rated Power:
- USB Port 1: 18 Watts Max. White port.
- USB Port 2: 18 Watts Max. Green port.